SWITCH



ERD SERIES

ROTARY TYPE SEALED CONSTRUCTION

PATENT NO: 61003

■ FEATURES

- Molded-in terminals and fully sealed construction.
- Standard 2.54mm pin spacing.
- UL 94V-0 grade fire retardant plastics.
- Reliable contact and long-term stability.
- Binary decimal (8 and 10 positions) and hexadecimal (16 positions) real and complimentary codes available.
- Pin-out compatible with most of current equivalents.
- Gold plated contact to ensure low contact resistance

■ SPECIFICATIONS

1 ELECTRICAL

- Max. load rating,
  Switching 25mA, 24VDC
  Non-switching 100mA, 50VDC.
- Contact resistance 100mΩ Max. at 5VDC, 10mA.
- Insulation resistance 1000MΩ min. at 100VDC
- Dielectric strength 250VAC for 1 minute

2 MECHANICAL AND ENVIRONMENTAL

- Temperature Rating
  Operating −25°C to +70°C
  Storage −40°C to +85°C
- Operating Force 500 gf-cm Max.
- Life 10000 cycles min. of operations.
- Vibration MIL-STD-202F, Method 204D
- Solderability After flux 230±5°C for 5±0.5 second 95% coverage.
- Soldering Heat For Through Hole Type
  260 ±5°C for 5±1 second.
  For Surface Mounting Type
  260±5°C for 10±1 second
  280±5°C for 2±0.5 second
  (Resistance to IR Reflow Soldering Heat)

■ CODE

PIN NO \ POSITION	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
1	○	●	○	●	○	●	○	●	○	●	○	●	○	●	○	●
2	○	○	●	●	○	○	●	●	○	○	●	●	○	○	●	●
4	○	○	○	○	●	●	●	●	○	○	○	○	●	●	●	●
8	○	○	○	○	○	○	○	○	●	●	●	●	●	●	●	●

● ..... Real Code
Rotor color: White

○ ..... Complimentary Code
Rotor color: Red

ERD 1 x x x x (Flat Type)

NEW



ERD 2 x x x x (Shaft Type)



■ DIMENSIONS AND CIRCUITRY

Unit: mm (inch)

Flat Type

ERD 1***S



ERD 2***S



P.C.B LAY OUT (TOP VIEW)

ERD ****S



NEW ERD ****M



NEW ERD 1***R



NEW ERD 2***R



ERD ****R



(SMT TYPE)

ERD****M



Shaft Type



NEW ERD 1***F



NEW ERD 2***F



ERD ****F



■ CONSTRUCTION



■ PART NUMBERING SYSTEM

ERD 1 10 R S

- *Setting:* *S: Standard type (Top Adjust type)*
  R: Right Angle type with row spacing 2.54mm
  F: Right Angle Type with row spacing 5.08mm
  M: Surface Mounting type with Top Tape Sealed
  D: Surface Mounting type with Top Tape Sealed in Tape & Reel Package
- *Code:* *R: Real*
  C: Complimentary
- *Number of Position:* *08*, *10*, *16*
- *Rotor:* *1: Flat type*
  2: Shaft type
- *Series name:* *ERD: Rotary Type Sealed Construction*

■ OPTIONS

1. Special marking available.
2. Shaft Cover
   118-80100 (White)
   118-80200 (Red)



3. Tape & Reel Packaging (per EIA STANDARD)

Flat type only





Each Reel contain 750 pcs switches with a 390mm minimum leader and a 160mm minimum trailer